

AUXILIARY CONTACT BLOCK F.3TB52 TO 3TB56,3TC52,  
3TC56 RIGHT

### Auxiliary circuit:

**Number of NC contacts / for auxiliary contacts**

- instantaneous switching

1

**Number of NO contacts / for auxiliary contacts**

- instantaneous switching

1

**Operating current / of the auxiliary contacts / at AC-15**

- at 230 V

A

5.6

### Installation/mounting/dimensions:

**Type of mounting**

snap-on mounting

### Connections:

**Design of the electrical connection**

- for auxiliary and control current circuit

screw-type terminals

### Certificates/approvals:

**General Product Approval**

**other**



CCC



CSA



GOST



UL

[Declaration of Conformity](#)

### Further information:

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/industrial-controls/catalogs>

**Industry Mall (Online ordering system)**

<http://www.siemens.com/industrial-controls/mall>

**Cax online generator:**

<http://www.siemens.com/cax>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<http://support.automation.siemens.com/WWW/view/en/3TY6561-1B/all>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3TY6561-1B](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3TY6561-1B)

last change:

Sep 24, 2012